



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 1 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name	Ikaros MOB Light & Smoke Mk IV
Article Nos.	345105
Chemical name	Contains 1350 g of pyrotechnic composition and a lithium battery.
Document number	SDS Ikaros MOB Light and Smoke Mk IV - ed1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use	Distress signal
Uses advised against	None specified

1.3. Details of the supplier of the safety data sheet

Company/Manufacturer	Hansson PyroTech AB / Nammo LIAB AB
Company address	P O Box 154, SE-711 23 Lindesberg, Sweden
E-mail, internet	info@hansson-pyrotech.com www.hansson-pyrotech.com
Telephone number	+46 581 871 00
Telefax number	+46 581 872 51

1.4. Emergency telephone number

Emergency telephone number	+46 581-87 111 (Available 24 hours)
Contact person	Ask for officer on duty at Nammo LIAB AB

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Main health hazard	Pyrotechnic device; will emit smoke and become hot (200°C). Hazards refer to contents of signal.
Inhalation	Smoke can be irritating.
Skin contact	Contact with hot gases or hot casing can cause burns.
Eye contact	Contact with smoke and/or ashes can be irritating.
Ingestion	If smoke composition from damaged signal is ingested, immediately take the patient to hospital.
Fire and explosive hazards	If exposed to flame the product will eventually ignite.
Environmental hazards	Large amounts of unburned smoke composition from damaged signals can be poisonous for aqueous organisms and cause long term effects in aquatic environments.



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 2 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

CLP Classification Explosive Division 1.4 – H204 Acute Toxic Category 4 – H332 Skin Irritant Category 2 – H315 Skin Sensitiser Category 1 – H317 Eye Irritant Category 2 – H319 STOT SE Category 3 – H335 Aqueous Chronic Category 2 – H411 For full wording of Hazard statements see Section 16	DPD Classification Explosive – R2 Harmful –R20/22-R36/37/38-R43 Hazardous for the Environment – R51/53 For full wording of Risk phrases see Section 16
---	---

2.2. Label elements

WARNING

Contains: Potassium chlorate and Solvent Orange 86

- H204 – Fire or projection hazard.
- H332 – Harmful if inhaled.
- H315 – Causes skin irritation
- H317 – May cause an allergic skin reaction
- H319 – Causes serious eye irritation.
- H335 – May cause respiratory irritation
- H411 – Toxic to aquatic life with long lasting effects



- P102 - Keep out of reach of children.
- P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- P280 - Wear protective gloves / protective clothing / eye protection / face protection.
- P501 – Dispose of contents / container to authorised waste disposal facility.
- P370+P378 - In case of fire: Use water for extinction.
- P309+P311 - If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

2.3. Other hazards

Contact with hot gases, hot casing or burning flare can cause severe burns.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous component(s)

Under CLP EC1272/2008

Identification on product	Substances	CAS No.	REACH Registration No.	%	Gram	CLP Hazard Category & H Statements
Ignition Composition:	Potassium Chlorate	3811-04-09	01-2119971261-41	40	20.0	Oxidising Solid Cat 1 – H271 Acute Toxic Cat 4 – H302, H332 Aquatic Chronic Cat 2 – H411



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 3 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

Smoke Composition:	Potassium Chlorate	3811-04-09	01-2119971261-41	35	455.0	Oxidising Solid Cat 1 – H271 Acute Toxic Cat 4 – H302, H332 Aquatic Chronic Cat 2 – H411
	Solvent Orange 86	81-64-1	01-2119494917-18	40	520.0	Skin Sensitiser Cat 1 – H317 Eye Irritant Cat 2 – H319 Skin Irritant Cat 2 – H315 STOT SE Cat 3 - H335
Lithium Battery:	Lithium Metal	7439-93-2	01-2119966143-38	-	0.74	Water-react. 1 – H260 Skin Corr. 1B – H314
	Manganese Dioxide	1313-13-9	01-2119452801-43	-	22.2	Acute Toxic Cat 4 – H302, H332

Under DPD EC1999/45

Identification on product	Substances	CAS No.	%	Gram	Risk phrases
Ignition Composition:	Potassium Chlorate	3811-04-09	40	20.0	O,Xn,N: R 9-20/22-51/53
Smoke Composition:	Potassium Chlorate	3811-04-09	35	455.0	O,Xn,N: R 9-20/22-51/53
	Solvent Orange 86	81-64-1	40	520.0	Xi: R36/37/38-43
Lithium Battery:	Lithium Metal	7439-93-2	-	0.74	F,C: R 14/15-34
	Manganese Dioxide	1313-13-9	-	22.2	Xn: R 20/22

For full wording of H-statements and R-phrases see Section 16.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

After inhalation

Move patient to fresh air.



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 4 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

After skin contact	If burned, wash with plenty of water for at least 20 min.
After eye contact	Keep eyelids apart. Wash with a lot of water. If needed visit physician.
After ingestion	Contact a physician.

4.2. Most important symptoms and effects, both acute and delayed

Contact with hot tube can cause burns. Harmful if inhaled. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

None other than above.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

- Suitable extinguishing media Use any fire extinguishing media at early stages of fire. Once the product has ignited it cannot be extinguished.
- Not to be used No restriction.

5.2. Special hazards arising from the substance or mixture

The products emit thick orange smoke that can be ignited in a confined space.

5.3. Advice for fire-fighters

Breathing aid.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Normal industrial hygiene, use protective gloves.

6.2. Environmental precautions

Do not let waste reach drains, sewers and bodies of water or leak into ground.

6.3. Methods and material for containment and cleaning up

Collect using non-sparking tools, reuse if undamaged. Otherwise, keep for disposal by experts.

6.4. Reference to other sections

See Sections 8 & 13.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid dropping the signal on hard surfaces.



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 5 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

7.2. Conditions for safe storage, including any incompatibilities

Storage Temperature should not exceed +75° C

7.3. Specific end use(s)

Distress signal

SECTION 8 PERSONAL PROTECTION/EXPOSURE CONTROLS

8.1. Control parameters

None set

8.2. Exposure controls

Recommended engineering controls	No fire, sparks or welding close to the items. If cleaning up spillage, use tools which can not strike sparks.
Personal protective equipment	Normally none needed. But in case of spillage:
- Respiratory protection	In case of dust use particle filter mask such as EN143 Type P or EN149 Type FFP-S.
- Hand protection	Leather or similar protective gloves.
- Eye protection	Shatter-proof glasses or goggles.
- Skin protection	Normal industrial hygiene
Specific hygiene measures	No smoking.
Further information	Always check applicability with your supplier of protective equipment.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Yellow aluminium tube inserted in a yellow plastic float body with an orange band, two opaque lamp bulbs, orange label and black ignition mechanism.
Odour	None
Odour threshold value	Not applicable
pH (concentrated product)	Not applicable
Melting point (°C)	Not determined
Boiling point/range (°C)	Not applicable
Flash point (°C)	Not applicable
Evaporation rate	Not applicable
Flammability	Contents are flammable
Explosive properties	Pyrotechnic smoke generator. Also contains lithium



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 6 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

	battery.
Vapour pressure (mbar at 25°C)	Not applicable
Vapour density	Not applicable
Density at 20°C (g/cm ³)	Not determined
Solubility in water (% by weight)	Insoluble
Solubility in solvents	Not determined
Partition coefficient (log Pow)	Not applicable
Autoignition temperature (°C)	> 200
Decomposition temperature (°C)	Not determined
Viscosity	Not applicable
Oxidising properties	Contents have oxidising properties

9.2. Other information

Note: These are typical values and do not constitute a specification

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Stable product under recommended storage and handling conditions.

10.2. Chemical stability

Stable product under recommended storage and handling conditions.

10.3. Possibility of hazardous reactions

Stable product under recommended storage and handling conditions. If spillage from damaged signals comes in contact with sulphuric acid, spontaneous ignition can occur!

10.4. Conditions to avoid

High temperatures, above 100 °C

10.5. Incompatible materials

Sulphuric acid

10.6. Hazardous decomposition products

Pyrotechnic device; will emit smoke and become hot (200°C).

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available on mixture. Data based on individual components shown below.



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 7 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

Hazardous ingredients	Potassium chlorate and Solvent Orange 86.
(a) acute toxicity	Potassium chlorate: LD ₅₀ oral rat 1870 mg/kg - Harmful by ingestion Calculated product ATE = 17474 mg/kg – Not harmful by ingestion Potassium chlorate: ATE inhalation 1.5 mg/l Calculated product ATE = 3.9 mg/l – Harmful by inhalation
(b) skin corrosion/irritation	Classified as Skin Irritant Category 2 under CLP due to presence of Solvent Orange 86
(c) serious eye damage/irritation	Classified as Eye Irritant Category 2 under CLP due to presence of Solvent Orange 86
(d) respiratory or skin sensitisation	Classified as a Skin Sensitiser Category 1 under CLP due to presence of Solvent Orange 86
(e) germ cell mutagenicity	No deleterious effects known.
(f) carcinogenicity	No deleterious effects known.
(g) reproductive toxicity	No deleterious effects known.
(h) STOT-single exposure	Classified as a Respiratory Irritant Category 3 under CLP due to presence of Solvent Orange 86
(i) STOT-repeated exposure	No deleterious effects known.
(j) aspiration hazard	No deleterious effects known.
Likely routes of exposure	Contact with skin
Symptoms related to the physical, chemical and toxicological characteristics	Powders are irritating to the skin, eyes and respiratory tract. May cause sensitisation by skin contact. May cause gastric irritation, nausea and vomiting.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	No deleterious effects known.
Other information	None

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No data available on mixture. Data based on individual components shown below.

Potassium chlorate EC₅₀ Daphnia magna 24h: 1.093mg/l Toxic.

12.2. Persistence and degradability

Not applicable – contains inorganic materials and is in form of solid article.

12.3. Bioaccumulative potential



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 8 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

Mobility No test data on product.

12.4. Mobility in soil

None – product in form of solid article.

12.5. Results of PBT and vPvB assessment

Does not fulfil the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

Not a Marine pollutant (IMDG Code).

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal of waste materials

Waste should be kept in separate container. NO SMOKING!

Destruction must only be done by experts. Used product may be disposed as ordinary plastic/metallic waste.

DO NOT TRY TO DISMANTLE THE PRODUCT!

Contaminated packing

May burn rapidly.

SECTION 14 TRANSPORT INFORMATION

14.1. UN numbers

See table below

14.2. UN proper shipping name

See table below

14.3. Transport hazard class(es)

See table below

14.4. Packing group

Not applicable

14.5. Environmental hazards

None

14.6. Special precautions for user

See P Statements in Section 2.2



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 9 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

US Market

Transport Classification

In Fibre Board Box

In Fibre Board Box

Article Number (Order article No.)

345105

345105

- UN No.

0197

0507

- Proper shipping name

Signals, smoke

Signals, Smoke

- Transport Class

1.4G

1.4S

- Packing Instruction

P135

P135

Label



IMO-IMDG code

- EMS code

F-B, S-X

F-B, S-X

EX number
(DOT/USA)

EX2005040230

N/A

MSB (Swedish Civil
Contingencies
Agency) Cert. No.

711/3825/2004

2009-4272

Comment

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

None specified

15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out on this mixture.

SECTION 16 OTHER INFORMATION

Inventories -

All ingredients listed in EINECS.

Sources of data used in this SDS

In-house data files



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 10 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

Literature such as Sax's Dangerous Properties of Industrial Materials, the RSC Dictionary of Substances and their Effects, RTECS
CLP Annex VI Tables 3.1 & 3.2
Suppliers' Safety Data Sheets
EU ESIS web site

Version number	2
Date prepared	24.10.14
Supersedes Version	1 dated 30.09.13
Nature of revision	REACH registration numbers introduced for potassium chlorate, solvent orange 86, lithium metal and manganese dioxide.

Mixture classified under CLP (EC1272/2008) by calculation based on ingredient information.

R-phrases used in document

R2	Risk of explosion by shock, friction, fire or other sources of ignition
R9	Explosive when mixed with combustible material
R14/15	Reacts violently with water, liberating extremely flammable gases
R20/22	Harmful by inhalation and if swallowed
R34	Causes burns
R36/37/38	Irritating to eyes, respiratory system and skin
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

H-statements used in document

H204	Fire or projection hazard
H260	In contact with water releases flammable gases which may ignite spontaneously
H271	May cause fire or explosion; strong oxidiser
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects



Safety Data Sheet

Issued by Atp	Department R&D	Date 24 October 2014	Page no 11 (11)
Product denomination Ikaros Man-Overboard (MOB) Light & Smoke Signal Mk IV		Document no. SDS Ikaros MOB Light and Smoke Mk IV	Edition no. 2

Supersedes: version 1 dated 30 September 2013

Based on EU Regulation 1907/2006 as amended by 453/2010

The current Material Safety Data Sheet was defined by Hansson PyroTech AB on the basis of knowledge of the product at the date of issue.

Therefore, data provided in this form can not be considered as exhaustive.

It is the duty of the operator

- to develop under his own responsibility, the safety dispositions regarding the operation of the product taking into account the data from this form
- to pass to all users and operators the appropriate safety data and warning regarding the risks mentioned in the documentation relative to the utilisation of the product
- to be cautious of possible risks faced when the product is used for other utilisation than those for which it has been designed